

B25C 960x960




- Cabinet type: Straight Curved 45°
- Size : 960(W)*960(H)*77(D) mm
- Material : aluminium profile
- Use environment : outdoor billboard
- Cabinet weight : 4 or 10kg
- Maintenance : front and rear service
- Connection type : HUB or cable connection

Product Characteristics



- Other Size: 1280*960/1280*640/480*960/640*640/640*960
- Arc size: 480*960
- flexible adjustment of connector plate holes
- Right angle size: (480+480)*960/(480+480)*640



Horizontal control box



casingless design

Product Parameter

Pixel Pitch	P2.5 outdoor	P3.076 outdoor	P4 outdoor	P4.44 outdoor	P5 outdoor	P6.67 outdoor	P8 outdoor	P10 outdoor
Cabinet Size(mm)	960*640	1960*640	960*640/960*960	960*960	960*960	960*960	960*960	960*960
Module Size(mm)	160*640	160*640	160*640	160*960	160*960	160*960	160*960	160*960
Module Resolution	64*256	52*208	40*160	36*216	32*192	24*144	20*120	16*96
Scan Mode	16S	13S	10S	9S	8S	6S	5S	2S
LED Configuration	1415	1415	1921	1921	1921	2727	2727	2727
Brightness(nit)	> 5000	≥5000	> 6000	≥6000	> 6500	≥6500	≥6500	≥6500
Driving Method	constant current	constant current	constant current	constant current	constant current	constant current	constant current	constant current
Refresh Rate	> 3840	≥3840	> 3840	≥3840	> 3840	≥3840	≥3840	≥3840
Grey Scale	16bit	16bit	16bit	16bit	16bit	16bit	16bit	16bit
Constant Color Range	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion
Viewing Angle(H/V)	> 140°/ > 140°	≥140°/ ≥140°	> 140°/ > 140°	≥140°/ ≥140°	> 140°/ > 140°	≥140°/ ≥140°	≥140°/ ≥140°	≥140°/ ≥140°
Contrast Ratio	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1	5000:1
Module Input Voltage(V)	4.5-5	4.5-5	4.5-5	4.5-5	4.5-5	4.5-5	4.5-5	4.5-5
Module Max Current(A)	25	25	25	25	25	25	25	25
Max Power(W/m²)	700~800	700~800	700~800	700~800	700~800	700~800	700~800	700~800
Average Power(W/m²)	200~300	200~300	200~300	200~300	200~300	200~300	200~300	200~300
IP Level	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67
Input Voltage(V)	110~220	110~220	110~220	110~220	110~220	110~220	110~220	110~220
Display Weight	13±2kg	13±2kg	24±2kg	24±2kg	24±2kg	24±2kg	24±2kg	24±2kg
Display Thickness	93.5mm	93.5mm	94mm	94mm	94mm	96.5mm	96.5mm	96.5mm
Life Time(Hours)	≥100000	-20°C~+60°C	≥100000	≥100000	≥100000	≥100000	≥100000	≥100000
Working Temperature	-20°C~+60°C	10%-95%RH	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C
Working Humidity	10%-95%RH		10%-95%RH	10%-95%RH	10%-95%RH	10%-95%RH	10%-95%RH	10%-95%RH
Certification	FCC/CE/RoHS/BIS							

Note: * is input voltage shall depend on project installation site, please check with our sales representative.