

## E25D 500×1000



- Cabinet type: Straight/Curved
- Size: 500(W)\*1000(H)\*70(D) mm
- Material: die-casting aluminium
- Connection type: HUB connection
- Cabinet weight: 7.3kg
- Maintenance: front service
- Use environment: indoor/outdoor rental

### Product Characteristics



- Corner protection
- Seamless splicing
- High grey scale & High contrast
- The indicator light reflects the working status



Fast quick lock



Corner protection

### Product Parameter

| Pixel Pitch                | P1.953 indoor    | P2.604 indoor    | P2.84 indoor     | P3.91 indoor     | P2.84 outdoor    | P3.47 outdoor    | P3.91 outdoor    | P4.81 outdoor    |
|----------------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Module Size(mm)            | 250*250          | 250*250          | 250*250          | 250*250          | 250*250          | 250*250          | 250*250          | 250*250          |
| Module Resolution          | 128*128          | 96*96            | 88*88            | 64*64            | 88*88            | 72*72            | 64*64            | 52*52            |
| Scan Mode                  | 32S              | 32S              | 22S              | 16S              | 22S              | 18S              | 16S              | 13S              |
| LED Configuration          | 1515             | 2121             | 2121             | 2121             | 1921             | 1921             | 1921             | 1921             |
| Brightness(nit)            | ≥600             | ≥600             | ≥600             | ≥600             | ≥4000            | ≥4000            | ≥4000            | ≥4000            |
| Driving Method             | constant current | constant current | constant current | constant current | constant current | constant current | constant current | constant current |
| Refresh Rate               | ≥3840            | ≥3840            | ≥3840            | ≥3840            | ≥3840            | ≥3840            | ≥3840            | ≥3840            |
| Grey Scale                 | 16bit            | 16bit            | 16bit            | 16bit            | 16bit            | 16bit            | 16bit            | 16bit            |
| Constant Color Range       | 281 trillion     | 281 trillion     | 281 trillion     | 281 trillion     | 281 trillion     | 281 trillion     | 281 trillion     | 281 trillion     |
| Viewing Angle(H/V)         | ≥170°/≥170°      | ≥170°/≥170°      | ≥170°/≥170°      | ≥170°/≥170°      | ≥160°/≥140°      | ≥160°/≥140°      | ≥160°/≥140°      | ≥160°/≥140°      |
| Contrast Ratio             | 1000:1           | 1000:1           | 1000:1           | 1000:1           | 5000:1           | 5000:1           | 5000:1           | 5000:1           |
| Module Input Voltage(V) 5V | 5V               | 5V               | 5V               | 5V               | 5V               | 5V               | 5V               | 5V               |
| Module Max Current         | 4.5A             | 4.5A             | 4.5A             | 4.5A             | 7.8A             | 7.8A             | 7.8A             | 7.8A             |
| Max Power(W/m²)            | 382              | 382              | 382              | 382              | 662              | 662              | 662              | 662              |
| Average Power(W/m²)        | 127              | 127              | 127              | 127              | 221              | 221              | 221              | 221              |
| IP Level                   | IP54             | IP54             | IP54             | IP54             | IP67             | IP67             | IP67             | IP67             |
| Input Voltage(V)*          | 110~220          | 110~220          | 110~220          | 110~220          | 110~220          | 110~220          | 110~220          | 110~220          |
| Display Weight             | 13.2kg           | 13.2kg           | 13.2kg           | 13.2kg           | 13.5kg           | 13.5kg           | 13.5kg           | 13.5kg           |
| Display Thickness          | 82mm             | 82mm             | 82mm             | 82mm             | 82mm             | 82mm             | 82mm             | 82mm             |
| Life Time(Hours)           | ≥100000          | ≥100000          | ≥100000          | ≥100000          | ≥100000          | ≥100000          | ≥100000          | ≥100000          |
| Working Temperature        | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      |
| Working Humidity           | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        |
| Certification              | FCC/CE/RoHS/BIS  |                  |                  |                  |                  |                  |                  |                  |

Note: \* is input voltage shall depend on project installation site, please check with our sales representative.