

F25C 600x337.5

Product Parameter

| Pixel Pitch             | P0.93 indoor     | P1.25 indoor     | P1.56 indoor     |
|-------------------------|------------------|------------------|------------------|
| Module Size(mm)         | 150*168.75       | 150*168.75       | 150*168.75       |
| Module Resolution       | 160*180          | 120*135          | 96*108           |
| Scan Mode               | 54S              | 60S              | 54S              |
| LED Configuration       | COB              | COB              | COB              |
| Brightness(nit)         | ≥600             | ≥600             | ≥600             |
| Driving Method          | constant current | constant current | constant current |
| Refresh Rate            | ≥3840            | ≥3840            | ≥3840            |
| Grey Scale              | 16bit            | 16bit            | 16bit            |
| Constant Color Range    | 281 trillion     | 281 trillion     | 281 trillion     |
| Viewing Angle(H/V)      | ≥170°/≥170°      | ≥170°/≥170°      | ≥170°/≥170°      |
| Contrast Ratio          | 1000:1           | 1000:1           | 1000:1           |
| Module Input Voltage(V) | 4.5-5            | 4.5-5            | 4.5-5            |
| Module Max Current(A)   | 1.2~1.5          | 1.2~1.5          | 1.2~1.5          |
| Max Power(W/m²)         | 250~280          | 250~280          | 250~280          |
| Average Power(W/m²)     | 50~90            | 50~90            | 50~90            |
| IP Level                | IP42             | IP42             | IP42             |
| Input Voltage(V)        | 110~220          | 110~220          | 110~220          |
| Display Weight          | 4kg              | 4kg              | 4kg              |
| Display Thickness       | 29.2mm           | 29.2mm           | 29.2mm           |
| Life Time(Hours)        | ≥100000          | ≥100000          | ≥100000          |
| Working Temperature     | -20°C~+60°C      | -20°C~+60°C      | -20°C~+60°C      |
| Working Humidity        | 10%~60%RH        | 10%~60%RH        | 10%~60%RH        |
| Certification           | FCC/CE/RoHS/BIS  |                  |                  |

Note: \* is input voltage shall depend on project installiatiion site, please check with our sales representative.



- Cabinet type: Straight
  - Size : 600(W)\*337.5(H)\*27(D) mm
  - Material : die-casting aluminium
  - Use environment : indoor fine pitch
- Cabinet weight : 2.5kg
  - Maintenance : front service
  - Connection type : HUB connection

Product Characteristics

- Die-cast plastic parts back cover
- High grey scale & high constrast
- Ultra-thin and lightweight
- Quickly install with back frame



Position Pin