

P25B 1280X1920



- Cabinet type: Tri-fold poster
- Size : 1280(W)*1920(H)*45(D) mm
- Material : aluminum profile & iron
- Use environment : poster display
- Cabinet weight : 45kg
- Maintenance : rear service
- Connection type : cable connection

Product Characteristics

- High grey scale & High contrast
- With wheels,easy to move
- Asynchronous remote control



Base with wheels



Foldable design

Product Parameter

Pixel Pitch	P1.25 indoor	P1.538 indoor	P1.86 indoor	P2 indoor	P2.5 indoor
Module Size(mm)	320*160	320*160	320*160	320*160	320*160
Module Resolution	256*128	208*104	172*86	160*80	128*64
Scan Mode	64S	52S	43S	40S	32S
LED Configuration	1010(GOB) or COB	1010(GOB) or COB	1515(GOB) or COB	1515(GOB)	2020(GOB)
Brightness(nit)	≥600	≥600	≥600	≥600	≥600
Driving Method	constant current	constant current	constant current	constant current	constant current
Refresh Rate	≥3840	≥3840	≥3840	≥3840	≥3840
Grey Scale	16bit	16bit	16bit	16bit	16bit
Constant Color Range	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion
Viewing Angle(H/V)	≥170°/≥170°	≥170°/≥170°	≥140°/≥140°	≥140°/≥140°	≥140°/≥140°
Contrast Ratio	1000:1	1000:1	1000:1	1000:1	1000:1
Module Input Voltage(V)	5V	5V	5V	5V	5V
Module Max Current	3.5A	3.5A	3.5A	3.5A	3.5A
Max Power(W/PCS)	850	850	850	850	850
Average Power(W/PCS)	285	285	285	285	285
IP Level	IP42	IP42	IP42	IP42	IP42
Input Voltage(V)	110~220	110~220	110~220	110~220	110~220
Display Weight	70kg	70kg	70kg	70kg	70kg
Display Thickness	60mm	60mm	60mm	60mm	60mm
Life Time(Hours)	≥100000	≥100000	≥100000	≥100000	≥100000
Working Temperature	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C
Working Humidity	10%~95%RH	10%~95%RH	10%~95%RH	10%~95%RH	10%~95%RH
Certification	FCC/CE/RoHS/BIS				

Note: * is input voltage shall depend on project installation site, please check with our sales representative.