

P25C 640x1920



- Cabinet type: double folded poster
- Size : 640(W)*1920(H)*45(D) mm
- Material : die-casting aluminium & iron
- Use environment : poster display
- Cabinet weight : 35.5kg
- Maintenance : front service
- Connection type : cable connection

Product Characteristics



- Magnetic folding border
- Asynchronous remote control
- Quickly install the lock
- Other size: 640*2400mm



Activity Wheel

Product Parameter

Pixel Pitch	P1.25 indoor	P1.538 indoor	P1.86 indoor	P2 indoor	P2.5 indoor
Module Size(mm)	320*160	320*160	320*160	320*160	320*160
Module Resolution	256*128	208*104	172*86	160*80	128*64
Scan Mode	64S	52S	43S	40S	32S
LED Configuration	1010(GOB)	1010(GOB)	1515(GOB)	1515(GOB)	1515/2020(GOB)
Brightness(nit)	≥600	≥600	≥600	≥600	≥600
Driving Method	constant current	constant current	constant current	constant current	constant current
Refresh Rate	≥3840	≥3840	≥3840	≥3840	≥3840
Grey Scale	16bit	16bit	16bit	16bit	16bit
Constant Color Range	281 trillion	281 trillion	281 trillion	281 trillion	281 trillion
Viewing Angle(H/V)	≥140°/≥140°	≥140°/≥140°	≥140°/≥140°	≥140°/≥140°	≥140°/≥140°
Contrast Ratio	1000:1	1000:1	1000:1	1000:1	1000:1
Module Input Voltage(V)	4.5~5	4.5~5	4.5~5	4.5~5	4.5~5
Module Max Current(A)	3~4	3~4	3~4	3~4	3~4
Max Power(W/㎡)	350~400	350~400	350~400	350~400	350~400
Average Power(W/㎡)	120~150	120~150	120~150	120~150	120~150
IP Level	IP42	IP42	IP42	IP42	IP42
Input Voltage(V)*	110-240	110-240	110-240	110-240	110-240
Display Weight	55kg	55kg	55kg	55kg	55kg
Display Thickness	62mm	62mm	62mm	62mm	62mm
Life Time(Hours)	≥100000	≥100000	≥100000	≥100000	≥100000
Working Temperature	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C	-20°C~+60°C
Working Humidity	10%~95%RH	10%~95%RH	10%~95%RH	10%~95%RH	10%~95%RH
Certification	FCC/CE/RoHS/BIS				

Note: * is input voltage shall depend on project installation site, please check with our sales representative.